



NovoDS

Make it Simple. Deliver your Message. Capture your Audience.

- An easy-to-manage digital signage solution for creating dynamic multimedia content
- Complete with a user-friendly interface to generate signage content with text, photos, audio, video, feeds, widgets, IP streams, USB and IP camera feeds — programming skills not required
- Fully customizable configuration for a variety of settings including, but not limited to, corporate, commercial, educational facilities and public installations
- 36 signage templates for easy content creation and one custom template for simple creative control
- Full HD 1080p at 60FPS display quality with support for the next generation of ultra-high resolution, 4K Ultra HD (3840 x 2160) displays from USB or a microSD card
- Display content directly from the built-in storage, microSD card or USB flash drive
- Export and update signage content via an Ethernet wired or wireless connection
- Network-based remote management and maintenance software included
- Manage and monitor the status of content playing from a single display to Enterprise wide with real-time updates. Multi-playlist scheduling and remote snapshot of content playing for live viewing
- Compatible with Windows[®] and Mac[®] operating systems
- Plug-n-play to display for easy setup and configuration
- Kensington[®] security slot to prevent theft or movement of the device

Your information, everywhere you want it to be



DIGITAL SIGNAGE



SPECIFICATIONS

Model Number	Vivitek NovoDS	
Product Compatibility	All Display Devices with HDMI Input	
Display Resolutions	1280 x 20 (16:9, 720p at 60 FPS), 1920 x 1080 (16:9, 1080p at 60 FPS), 3840 x 2160 (16:9, 4K Ultra HD [with microSD Card or USB] at 30 FPS)	
Output Orientation	Portrait, Landscape	
Storage	Internal: 8GB (5.1 GB User Availability) External: microSD Card (up to 32GB), USB Flash Drive	
Network Connection	Wi-Fi: 802.11 a/c (2.4 GHz & 5 GHz), Ethernet	
Media Formats Supported	Images	JPEG, PNG, GIF, BMP
	Video	MP2, MP4, H.264, VC-1 (WMV)
	Audio	MP3, WMA, AAC
	Other	Scrolling Text with Custom Visual Effects
Input / Output Connection Ports	USB 2.0 Type A, HDMI v1.4, microSD Card, RJ45 (10/100 Ethernet) , microUSB Power Input (5V/2A)	
LED Indicator	Green: System Power on; Red: System in Standby; Blue: Network Activity	
Button / Switch	Reset Button	
Power Supply / Consumption (AC Adapter)	100 ~ 240 V AC, 50/60 Hz, DC output: 5.35V and 2A	
Power Consumption	10W	
Accessories	USB Power Adapter, HDMI Cable, Power Cable, Remote Control , Mounting Bracket	
OS Platform Support	Windows® 7.0+, Mac® 10.7+	
Available Color	Dual-Tone: Black and Gray	
Security Solutions	Kensington® Security Slot	
Weight	128g (0.28 lbs)	
Dimensions (L x W x H)	120mm x 75mm x 26mm (4.7' x 2.9' x 1.0')	

© Copyright 2014 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.