



Go boundless. Converge voice, video, team chat, messaging, and more.



Technologies are constantly revolutionizing the way businesses communicate. More and more businesses realize that they need something beyond just a PBX in their digital transformation strategy. The aspiration to remain competitive press them to look for a system that breaks down the barriers of distance and embraces flexibility and customization.

For businesses that have higher expectations of a sophisticated communication system, they need a professional, reliable, and adaptable PBX system in place. Lack of efficiency-enhancing features, poor user experience, and inability to adapt to the fast-paced business environment make a communication system less desirable.

PBX Plus More Values and Possibilities

Yeastar addresses the challenges through the P-Series Phone System, an all-encompassing "PBX Plus More" solution that ensures uninterrupted communication for businesses. Beyond just a PBX, it provides visualized call management, video communications, advanced call center features, unified communications applications, anywhere anytime connectivity, omnichannel messaging, and everything practical yet outperforming across browsers, mobiles, and desktops.

Available in the Appliance, Software, and Cloud Edition, P-Series provides flexible deployment options, allowing you to have it sited on-premises or in the cloud. Balancing costs and future growth, it requires a lower total cost of ownership, less training, and fewer management efforts.

Third-party technologies including IP Phones, CRM, Microsoft Teams, Outlook, directory services, and PMS can also be integrated easily with the P-Series to form a cohesive communication and collaboration solution and break the boundary of systems.

Optimized with the right set of features, ease of use and management, future-proof flexibility and adaptability, P-Series unifies voice, video, team chat, messaging, and more to facilitate boundless communications.

Beyond just a PBX

- Cloud-based and on-premises options with minimal setup hassle
- Deliver, manage, and monitor services through Yeastar Central Management
- Regardless of distance and the choice of device
- Superior telephony features covering the must-haves to nice-to-haves
- Integrated video conferencing for engaging remote meetings
- Messaging integration for an omnichannel customer experience
- An open and integrated model that embraces more possibilities
- Streamlined operations with visual call activities
- Panel-based administration that makes things straightforward
- Granular permission based on different user roles
- Built-in security mechanism to minimize system vulnerabilities



PBX Plus UC Clients

Designed to enhance communication experience and efficiency, Linkus UC Clients allow P-Series users to easily access a comprehensive suite of calling, conference, voicemail, presence, enterprise contacts, collaboration from a single interface using web browsers, mobile phones, and desktops. Employees can stay connected with colleagues and customers where, when, and however they prefer.

PBX Plus Video Communications

P-Series Phone System makes remote face-to-face communications instant, simple, secure, and engaging with the integrated 1:1 web video call and video conferencing features. Through a multimedia environment for interactive virtual conferences, SMEs can benefit from a more engaging meeting experience along with the integrated screen sharing, inmeeting team chat, and more.

3 PBX Plus Call Center

P-Series Phone System introduces an inbound call center solution to improve agent efficiency, responsiveness, and ultimately customer satisfaction for SMEs running service centers. Besides standard communications features, Call Distribution, Queue Panel, Wallboard, SLA, and Call Reports are all designed to support more proactive performance monitoring, reporting, and management.

6 PBX Plus Operator Panel

The Operator Panel is a visualized console for corporate operators and receptionists to quickly handle incoming calls based on the real-time availability of employees. They can simply drag and drop on the panel to dispatch calls to extensions, ring groups, and queues. Besides, the flexible rolebased permissions make it helpful under various scenarios by facilitating great effectiveness.



4 PBX Plus Presence & IM

As fundamental parts of unified communications, Presence and IM help businesses realize contextual collaboration and level up productivity. The Presence feature in the P-Series comes with rich information about users' availability and great flexibility in switching the status while the IM feature, along with file sharing, complements other forms of communication and prompt employee engagement.

7 PBX Plus Contacts Directory

P-Series Phone System makes it easy to organize contacts. Users can create and manage a companywide directory and personal contact entries. Both are synced across Linkus UC Clients, IP phones, and the PBX, enabling easy access and dialing from anywhere. Each department have separate permissions to different phonebooks with CRM contacts automatically synced and updated.

5 PBX Plus Omnichannel Messaging

By integrating digital communications channels such as WhatsApp and SMS, P-Series allows businesses to manage all customer messages in one place through Linkus UC Clients. Users can quickly respond to customer queries, transfer chat conversations to team members, and send messages to customers, providing an omnichannel customer experience.

PBX Plus Integrated System

Besides built-in functionalities, P-Series Phone System can also work with 3rd party technologies, including standard SIP endpoints, headsets, CRM, helpdesk, directory services, Microsoft Teams, Outlook, PMS, and more, to break the barriers among a wide variety of systems, deliver a unified experience with unmatched simplicity and new possibilities.



FEATURES

	Standard Plan	Enterprise Plan	Ultimate Plan
Deployment Mode	Appliance	Appliance, Software, Cloud	Appliance, Software, Cloud
Telephony Features	•	•	•
Business Features	•	•	•
Administration & Security	•	•	•
Unified Communications	•	•	•
Team Chat	•	•	•
Remote Access Service*	•	•	•
Custom PBX Domain Name (FQDN)	•	•	•
Remote, Secure PBX Web Portal Access	•	•	•
Linkus UC Clients Remote Connection	•	•	•
LDAP Server Remote Access	•	•	•
Remote SIP Service*		•	•
Easy Remote SIP Endpoints Registration*		•	•
WebRTC Trunk		•	•
Advanced Call Center Features		•	•
Queue Panel & Customizable Wallboard		•	•
Queue Callback for Reduced Call Abandonment		•	•
SLA for Performance Measurement		•	•
Insightful Call Center Reports		•	•
Omnichannel Messaging		•	•
Customer Messages in One Chat Panel		•	•
Message to Queue & Chat Transfer		•	•
Automatic Contacts Matching		•	•
Message Detail Records			
Supporting WhatsApp and SMS		•	•
Phonebooks		•	•
Call Accounting		•	•
Voicemail Announcement		•	•
CRM and Helpdesk Integration		•	•
Contacts Synchronization, Call Pop-up, Call Journal, Click to Call		•	•
Supporting HubSpot, Zoho CRM, Salesforce, Bitrix24, and Odoo, Zoho Desk, and Zendesk		•	•
Microsoft 365 Integration		•	•
Azure Active Directory Integration		•	•
User Sync & Single Sign-on (SSO)		•	•
Microsoft Teams Integration		•	•
Outlook Integration		•	•
API		•	•
Windows Active Directory Integration			•

Video Conferencing			•
Bulk Email & Instant Link Invitation			•
HD Audio and Video			•
Screen Sharing and In-meeting Team Chat			•
Video Calls			•
Linkus SDKs			•
Add Linkus Voice Calling to Custom Desktop/Mobile/Web Applications			•
APIs, Tools, Documentations, and Sample Codes			•
Disaster Recovery*			•
PMS Integration*	Optional	Optional	Optional

Built-in Features for All Plans	and the Appliance Edition		
Telephony Features	Business Features	Administration & Security	Unified Communications
Telephony Features Call Forwarding Call Transfer (Attended/Blind) Call Monitoring (Listen/Whisper/Barge-in) Call Parking Call Pickup Call Waiting Call Flip/Switch Call Merge IVR Queue Queue Priority Queue Call Logs Queue Missed Call Disposition Ring Group Paging & Intercom Conference Rooms CDR & Scheduled Download	Business Features Call Recording Support Scheduled Download to Remote FTP Server Call Allow/Block List BLF Support Busy Camp-on Business Hours & Holidays Boss-Secretary Custom Prompts Distinctive Ringtone Music on Hold MOH Playlist & Streaming T.38 Fax Fax to Email Voicemail LDAP Server PIN List Speed Dial	Administration Web-based GUI Dashboard Auto Provisioning User Role & Permission Extension Group & Organization Bulk Import & Export (Extension, Trunks, Route, Contacts) Operation Logs Event Logs & Notifications Backup and Restore Troubleshooting Built-in SMTP Server AMI (Asterisk Manager Interface) Network Drive SNMP Support	Unified Communications Linkus UC Clients Web Client Mobile Client (iOS & Android) Desktop Client (Windows & MacOS) Google Chrome Extension WebRTC Audio Call Function Keys on Web/Desktop Client Hotkeys on Desktop Client Remote Desk Phone Control (Linkus CTI Mode) Presence Contacts Management (Personal and Company) Audio Conferencing Door Phone Video
 Basic Call Reports Dial by Name AutoCLIP Caller ID CID-based & DID-based Call Routing DID (Direct Inward Dialing) DND (Do Not Disturb) DOD (Direct Outward Dialing) DNIS 	 Emergency Number Emergency Notifications IP Phone Concurrent Registrations Operator Panel Monitor Call Status Monitor Presence Status (Extension, Ring Group, Queue, Parking Slot) Drag & Drop to Dispatch Call Advanced Call Control 	Security Security SRTP & TLS Call Encryption Auto & Static Defense Global Anti-hacking IP Blocklist Certificates Password Policy Enforcement Two-factor Authentication Allowed Country IP's & Codes Outbound Call Frequency Restriction	Door Phone Video Preview Voicemail Voicemail Transcription Group Voicemail Voicemail to Email Pop-up URL Microsoft Teams Integration (via Call2Teams) Headset Integration

Note:

- 1) Remote Access Service, Remote SIP Service*: Since the Cloud Edition is inherently accessible from anywhere, Remote Access Service and Remote SIP Service are only for the Appliance and Software Edition.
- 2) **Easy Remote SIP Endpoints Registration***: Register your remote IP phones, branch office PBXs, VoIP gateways, and alike remote SIP endpoints to the PBX easily as if they were deployed on your PBX's intranet.
- Call Recording*: The Call Recording feature is free of charge on the Appliance and Software Edition. As for the Cloud Edition, each PBX instance comes with 500 free recording minutes and more can be purchased additionally if needed.
- 4) **Disaster Recovery***: Supported by the Software Edition and requires an additional PBX redundancy server to function.
- 5) **PMS Integration***: Supported by the Appliance Edition and Software Edition.

Cloud Edition

▼ Faster Time to Market

✓ Easier Service Delivery

✓ Easier Management



The increased interest in UCaaS is creating tremendous opportunities for MSP, VAR, and other channel partners alike. As a ready-to-go deployment option, Yeastar P-Series Cloud Edition is designed for service providers and telecom resellers to jump-start hosted voice business and drive revenue as fast as possible. With minimum upfront cost, technical expertise, and training, you can confidently deliver best-of-breed UCaaS while keeping complete ownership of customers.



Make the move from CapEx to OpEx

Yeastar eliminates the hassle and initial expenditure of setting up your own servers, thus reducing your risk of introducing a new service. With our partner-ready service delivery platforms, you are ready to sell to customers in a day with minimal investment and can easily scale up as your business grow. Whether serving a handful of users, or even thousands, that's not a problem.



On top of a high availability architecture

With redundant servers for real-time replication and seamless failover, load-balanced infrastructure for maximum resource utilization, SBC and other security mechanisms guarding against malicious attacks, there's no need to spend extra time, effort, and expense on the upkeep and maintenance of the delivery environment.



Speed up the roll-out of your service

Through Yeastar UCaaS service delivery and management platforms, it only takes a few clicks to create PBX instances of different capacities. With multiple nodes across the globe, you can select hosted servers closest to your customers. All your PBX instances' details are tracked in a list view, making it easy to manage the upgrade, renewal, resizing, and more within the same interface.



Customize & scale on-demand

As a prime opportunity to grow, this solution also enables you to create your own service packages, bundle IP phones and other hardware, and adds on SIP trunking and other services. Moreover, it is clicks away to scale up and down services and upgrade subscription plans for various needs, which in turn leads to a stickier customer relationship.



One interface for operating convenience

Besides viewing all PBX instances in a list view, you can edit them directly and create tasks to automatically perform PBX provisioning, upgrades, backups, and more for customers. The real-time information of cloud PBXs, tasks, alarms, and more is also displayed in a widget-based dashboard for you to learn how services are going on at a glance.



Spot issues before customers do

With central management platform automatically monitoring the status of all your customers' PBX instances, you get instant alerts when threats, security-related risks, or any other critical system issues occur, and can quickly diagnose and troubleshoot them before they hurt your bottom line. It ensures more seamless service while taking a lot of burden off your shoulders.



General Specifications & Server Requirements

Software Edition General Specifications

• • • •

Max. Extension	10,000	Operating System	Ubuntu 20.04 LTS	
Max. Concurrent Calls	1000	Activation Method	Online /Offline Activation	
Recommended Server	VMware Workstation 15.1.0 or late	r; VMware ESXi 6.0 or later; Hyper-V	10.0.17134.1 or later; KVM;	
Environment	Proxmox VE 7.0 or later; Amazon Web Service; Digital Ocean; Vultr; Alibaba Cloud; Dell EMC PowerEdge			

Virtual Machine Platform Requirements

Extension Number (Concurrent Calls)	1-10 (1-3)	11-20 (4-5)	21-30 (6-8)	31-40 (9-10)	41-50 (11-13)	51-150 (14-38)	151-300 (39-75)	301-500 (76-125)	501-1000 (126-250)
vCPU	2	2	2	2	2	2	4	6	8
CPU Frequency	2.4 GHz	2.4 GHz	2.4 GHz	2.4 GHz	2.4 GHz	2.4 GHz	2.4 GHz	2.4 GHz	3.0 GHz
Memory	2 GB	2 GB	4 GB	4 GB	4 GB	4 GB	4 GB	6 GB	16 GB
Storage (Call Recording Disabled)	10 GB	20 GB	30 GB	40 GB	50 GB	50 GB	50 GB	100 GB	200 GB
Storage (Call Recording Enabled)		Recommended: 1 TB The capacity requirement depends on your total recording volume, 1000 mins = 1GB							

Cloud Server Requirement

Extension Number (Concurrent Calls)	1-20 (1-5)	21-50 (6-13)	51-150 (14-38)	151-300 (39-75)	301-500 (76-124)	501-1000 (126-250)
vCPU	2	2	2	4	6	8
CPU Frequency	2.4 GHz	2.4 GHz	2.4 GHz	2.4 GHz	2.4 GHz	3.0 GHz
Memory	2 GB	4 GB	4 GB	4 GB	6 GB	16 GB
Storage (Call Recording Disabled)	40 GB	40 GB	50 GB	50 GB	100 GB	200 GB
Storage (Call Recording Enabled)	Recommended: 1 TB The capacity requirement depends on your total recording volume, 1000 mins = 1GB					

Hardware Server Requirement

Extension Number (Concurrent Calls)	1-1000 (1-250)	1001-2000 (251-500)	2001-4000 (501-1000)
Recommended Server	Dell EMC PowerEdge R350	Dell EMC PowerEdge R350	Dell EMC PowerEdge R750
CPU	 CPU: Intel(R) Xeon(R) E-2374G CPU Frequency: 3.70GHz CPU Count: 1 Cores: 4 Threads: 8 	 CPU: Intel (R) Xeon (R) E-2386G CPU Frequency: 3.50GHz CPU Count: 1 Cores: 6 Threads: 12 	 CPU: Intel (R) Xeon (R) Gold 6346 CPU Frequency: 3.10GHz CPU Count: 2 Cores: 16 Threads: 32
Memory	16 GB	16 GB	32 GB
Hard Disk	1 TB	1 TB	1 TB

For the server requirements for PBX of more than 1000 concurrent calls, please contact Yeastar for more details.



APPLIANCE EDITION

General Specifications

Appliances	P550	P560	P570	
Base Users / Max Users	50	50 100 / 200		
Max Concurrent Calls	25	30 / 60	60 / 120	
Base / Max Call Center Agents	50	100 / 200	300 / 500	
Max FXS Ports	8	8	16	
Max FXO/BRI Ports	8	8	16	
Max GSM/3G/4G Ports	4	4	6	
Max E1/T1/J1 Ports	-	1	2	
Expandable D30	0	1	2	
NFC Read/Write	Yes	Yes	Yes	
Ethernet Interfaces		2 x (10/100/1000 Mbps)		
Hard Disk	No	1 SATA (U	p to 2TB)	
USB	1 (USB Portable SSD, Up to 2TB) (USB Flash Drive, Up to 256)			
Power Supply	AC 100-240V 50/60HZ 0.6A max AC 100-240V 50/60HZ 1.5A max			
Size (L x W x H) (cm)	34 x 21 x 4.4	44 x 25.2 x 4.4	44 x 25.2 x 4.4	
Weight	1.64 KG	2.37 KG	2.38 KG	
Form Factor	1U Rackmount			
Environment	Operation Range: 0°C to 40°C, 32°F to 104°F Storage Range: -20°C to 65°C, -4°F to 149°F Humidity: 10-90% non-condensing			

