

QUICK OVERVIEW

TOUCHONE

General

- Meeting room management system
- Quick and easy installation and setup, no programming
- Built-in or on-wall installation

Compatibility

- Microsoft Office 365 ⁽¹⁾
- Microsoft Exchange ⁽²⁾ 2007 | 2010 | 2013 | 2016
- Google Apps for Work ⁽³⁾

Multilingual user interface

- Czech, Danish, English, French, German, Latvian, Russian, Spanish
- Other languages on demand



touchONE-5-B



touchONE-7-B



touchONE-7-M



touchONE-12-B



touchONE-12-M

	touchONE-5-B	touchONE-7-B	touchONE-7-M	touchONE-12-B	touchONE-12-M
Product code	CS0493	CS0494	CS0528	CS0495	CS0529
Display type	Color IPS LCD, LED backlit	Color a-Si TFT LCD, LED backlit	Color a-Si TFT LCD, LED backlit	Color a-Si TFT LCD, LED backlit	Color a-Si TFT LCD, LED backlit
Display size	4.3" (109 mm) diagonal	7" (177.8 mm) diagonal	7" (177.8 mm) diagonal	12.1" (307.3 mm) diagonal	12.1" (307.3 mm) diagonal
Resolution	800 x 480 pixels	1280 x 800 pixels	1280 x 800 pixels	1280 x 800 pixels	1280 x 800 pixels
Viewing angle	±80° horizontal, ±80° vertical	±80° horizontal, ±80° vertical	±80° horizontal, ±80° vertical	±80° horizontal, ±80° vertical	±80° horizontal, ±80° vertical
Touch technology	Projected capacitive	Projected capacitive	Projected capacitive	Projected capacitive	Projected capacitive
Sensors	Light and proximity	Light and proximity	Light and proximity	Light and proximity	Light and proximity
LED indicators	None	Green for free room Red for occupied room	Green for free room Red for occupied room	Green for free room Red for occupied room	Green for free room Red for occupied room
Network	Wired 10/100 BaseT Ethernet	Wired 10/100 BaseT Ethernet	Wired 10/100 BaseT Ethernet	Wired 10/100 BaseT Ethernet	Wired 10/100 BaseT Ethernet
Power supply	PoE, IEEE 802.3af / Class 0	PoE, IEEE 802.3af / Class 0	PoE, IEEE 802.3af / Class 0	PoE+, IEEE 802.3at / Class 4	PoE+, IEEE 802.3at / Class 4
Enclosure	Aluminum Edge-to edge front glass Protection IP30	Aluminum Edge-to edge front glass Protection IP30	Aluminum Edge-to edge front glass Protection IP30	Aluminum Edge-to edge front glass Protection IP30	Aluminum Edge-to edge front glass Protection IP30
Installation	Built-in, compatible with European and UK electrical wall boxes	Built-in, compatible with European, UK and US electrical wall boxes	On-wall, e.g. glass wall No wall drilling or cutting needed	Built-in, compatible with European, UK and US electrical wall boxes	On-wall, e.g. glass wall No wall drilling or cutting needed
Dimensions	136 x 81 x 37 mm When installed protrudes 11 mm	199 x 120 x 39 mm When installed protrudes 16 mm	199 x 120 x 26 mm When installed protrudes 26 mm	320 x 200 x 47 mm When installed protrudes 22 mm	320 x 200 x 33 mm When installed protrudes 33 mm
Weight	0.3 kg	0.6 kg	0.8 kg	2.0 kg	2.2 kg
Operating temperature	10° to 40° C	10° to 40° C	10° to 40° C	10° to 40° C	10° to 40° C
Relative humidity	10% to 90% non-condensing	10% to 90% non-condensing	10% to 90% non-condensing	10% to 90% non-condensing	10% to 90% non-condensing

⁽¹⁾ Microsoft Office 365 subscription is not a part of delivery.

⁽²⁾ Microsoft Exchange Server® is not a part of delivery.

⁽³⁾ Google Apps for Work subscription is not a part of delivery.