

## ErisTerminal® SIP Deskset

### VSP715

The compact VSP715 SIP deskset comes with all the essential features you need to keep pace with your business and your budget. Installation is easy and cost-effective with Power over Ethernet (PoE) support, dual Ethernet ports and auto-provisioning. Two programmable buttons provide one-touch access to shared call appearances, ACD, paging and more. Manage multiple calls with advanced call handling features and support for up to two SIP lines/accounts. Support for the G.722 wideband codec for HD Audio means you'll enjoy superior voice quality too.



### VSP715 Key Features

#### Advanced call handling

Impress customers with comprehensive call handling features that are compatible with hosted and open-source PBX platforms.\*

#### Flexibility

With support for up to two SIP lines/accounts, you can manage multiple calls with advanced call handling features.

#### Intuitive design

You're in business with a user-friendly interface, large backlit display, three soft keys and navigational pad.

#### Full-duplex speakerphone

Finally, a speakerphone that can keep up with your calls. Increase participation by allowing parties on both ends to speak and be heard – at the same time – for conversations that are more true to life.

#### HD voice quality

With G.722 wideband codec support for HD audio, calls have never sounded so rich and life-like.

#### Dual Ethernet ports

Do more with dual Ethernet ports. Connect your desktop computer or laptop to the phone – no need for extra cabling.

#### Power over Ethernet (PoE)

With PoE support, you can locate the phones anywhere that's convenient - no AC outlets or complicated wiring required.

#### Three-year warranty

Enjoy peace of mind that comes with an industry-leading, standard three-year warranty. VTech also provides advance replacement on warranty claims using new, not refurbished, products.

\*Compatible with Broadsoft®, Genband™, Metaswitch Networks and Asterisk-based platforms.



## Specifications, Weights and Dimensions

- Color: Black
- UPC: 735078034922
- Product dimensions (WxDxH):  
BS: 6.09" x 8.60" x 5.59"  
Corded HS: 8.09" x 1.99" x 2.05"  
HS on BS: 6.09" x 8.60" x 6.77"  
Footprint at 45 degree: 6.09" x 7.86" x 6.93"
- Product weight: 0.91 lbs.
- Giftbox dimensions (WxDxH):  
8.89" x 3.94" x 6.30"
- Giftbox weight: 2.27 lbs.
- Master pack dimensions (WxDxH):  
18.31" x 8.46" x 7.09"
- Master pack weight: 10.03 lbs.
- Quantity: 4

## Interface

- Dual Ethernet ports: 10/100 Mbps
- Base power: AC adapter (optional) and Class 2 Power over Ethernet (PoE)

## Display, Keys and Indicators

- 158 x 57 pixels (w x h) LCD resolution
- LCD backlighting (white)
- 3 soft keys
- 7 dedicated feature keys
- 2 programmable feature keys
- 4-way navigational pad
- Message waiting LED indicators

## Audio

- Full-duplex base speakerphone
- HAC Receiver
- 2.5 mm corded headset jack
- HD Voice for receiver

## Phone Features

- Supports up to 2 SIP account registrations
- Local phonebook up to 200 entries
- Phonebook import/export
- LDAP/Broadsoft® remote phonebook
- Call history up to 200 entries
- Shared Call Appearance (SCA)/ Bridged-Line Appearance (BLA)
- Do Not Disturb (DND)
- Busy lamp fields (BLF)

- 3-way local conference
- N-way network conference
- Call barring/blocking (block anonymous/blacklist)
- Dial plan/digit map
- Hotline
- Intercom
- Mute
- Redial
- 10 speed dial entries
- Call transfer: blind/attended
- Call hold
- Call park
- Call pick up
- Call forwarding: per-line basis (busy/always/no answer)
- Call timer (call duration)
- Caller ID
- Phonebook matching (incoming and outgoing calls)
- Multicast paging
- Multi-language support
- Automatic Call Distribution (ACD)

## Customization

- Soft key configuration
- Custom startup and idle logo
- Web interface configuration (admin & user)
- Custom default file

## Security

- 802.1x
- 802.1pq
- Transport Layer Security (TLS)
- AES encryption of config file for provisioning (128/64/32/16 bits)
- LLDP-MED

## Network

- STUN
- NAT
- RTP, SRTP
- SNTP
- VLAN
- Failover support and server redundancy
- Layer 3 QoS (ToS, Diffserv)

## Voice Codec

- G.711 a-law & u-law
- G.722
- G.726
- G.729

## Provisioning

- HTTP, HTTPS, FTP, TFTP
- DHCP options: 66, 159, 160
- PnP

## Maintenance

- Diagnostic: pcap trace
- Schedule resync: time and day setting
- Syslog

## Compatibility

- Broadsoft Broadworks®
- Asterisk-based platforms
- Metaswitch Networks
- Genband™

## Other

- 3-year standard warranty
- Optional AC adapter: VSP715-ADPT
- Advanced product replacement for warranty claims with new product